



	Characteristics				
	Name	Viscosity Grades	Technology	Specification & Approvals	Benefits
Hydraulic Oils	EQUIVIS ZS	32, 46, 68, 100	Mineral	DIN 51524-3 HVLP ISO 6743/4 HV AFNOR NF E 48-603 HV VICKERS M-2950S, -I-286	<ul style="list-style-type: none"> • Shear stable High Viscosity Index • Superior Thermal and oxidation stability • Extended oil drain interval
	AZOLLA AL	22, 46	Aluminum Non Staining	NSF H1 ACHENBACH	<ul style="list-style-type: none"> • No Stains performance for Aluminum and Yellow metals • Food grade approved
	AZOLLA AF	32, 46, 68	Mineral Zinc Free	DIN 51524 – 2 HLP ISO 6743/4 HM AFNOR NF E 48-603HM CINCINATTI MILACRON: P68, P69, P70 VICKERS M-2950, S-I-286 DENISON HF0, HF1, HF2 (T6H20C)	<ul style="list-style-type: none"> • Ashless HLP hydraulic oil for Enhanced Protection • Excellent filterability & Demulsibility • TOST LIFE: 6000+ Hours
	AZOLLA ZS	32, 46, 68	Mineral	DIN 51524 – 2 HLP ISO 6743/4 HM AFNOR NF E 48-603HM CINCINATTI MILACRON: P68, P69, P70 VICKERS M-2950, S-I-286 DENISON HF0, HF1, HF2 (T6H20C)	<ul style="list-style-type: none"> • High performance HLP Superclean hydraulic oil • Excellent filterability and wear protection • Extra Long Life • NAS LEVEL: 6 • TOST LIFE: 5000Hours
	ACANTIS HM	46, 68, 100, 150	Mineral	DIN 51524 – 2 HLP ISO 6743/4 HM VICKERS Z-104C DENISON HF0 IS 10522-1998	<ul style="list-style-type: none"> • Reliable performance HLP hydraulic oil. • Balanced antiwear and anti-oxidation properties • TOST LIFE: 2400 Hours